



Bearing No.	Boundary dimensions				Basic load ratings(kN)		Limiting speed		Mass
	mm				Dynamic	Static	rpm		kg
	d	D	B	r <sub>smin</sub>	Cr	Cor	Grease	Oil	
2200	10	30	14	0.6	7.3	1.59	19,000	23,000	0.047
2201	12	32	14	0.6	7.6	1.73	17,000	20,000	0.051
2202	15	35	14	0.6	7.7	1.85	15,000	18,000	0.06
2203	17	40	16	0.6	9.8	2.41	13,000	16,000	0.088
2204	20	47	18	1	12.6	3.3	12,000	14,000	0.14
2204K	20	47	18	1	12.6	3.3	12,000	14,000	0.137
2205	25	52	18	1	12.3	3.45	10,000	12,000	0.157
2205K	25	52	18	1	12.3	3.45	10,000	12,000	0.153
2206	30	62	20	1	15.2	4.5	8,600	10,000	0.256
2206K	30	62	20	1	15.2	4.5	8,600	10,000	0.25
2207	35	72	23	1.1	21.5	6.6	7,500	8,800	0.392
2207K	35	72	23	1.1	21.5	6.6	7,500	8,800	0.382
2208	40	80	23	1.1	22.3	7.35	6,700	7,900	0.493
2208K	40	80	23	1.1	22.3	7.35	6,700	7,900	0.482

<b>2209</b>	45	85	23	1.1	23.2	8.15	6,000	7,100	0.54
<b>2209K</b>	45	85	23	1.1	23.2	8.15	6,000	7,100	0.528
<b>2210</b>	50	90	23	1.1	23.2	8.45	5,500	6,400	0.583
<b>2210K</b>	50	90	23	1.1	23.2	8.45	5,500	6,400	0.569
<b>2211</b>	55	100	25	1.5	26.5	9.9	5,000	5,800	0.787
<b>2211K</b>	55	100	25	1.5	26.5	9.9	5,000	5,800	0.769
<b>2212</b>	60	110	28	1.5	34	12.6	4,600	5,400	1.08
<b>2212K</b>	60	110	28	1.5	34	12.6	4,600	5,400	1.06
<b>2213</b>	65	120	31	1.5	43.5	16.4	4,200	5,000	1.44
<b>2213K</b>	65	120	31	1.5	43.5	16.4	4,200	5,000	1.41
<b>2214</b>	70	125	31	1.5	44	17.1	3,900	4,600	1.52
<b>2215</b>	75	130	31	1.5	44.5	17.8	3,700	4,300	1.58
<b>2215K</b>	75	130	31	1.5	44.5	17.8	3,700	4,300	1.54
<b>2216</b>	80	140	33	2	48.5	19.9	3,400	4,000	1.99
<b>2216K</b>	80	140	33	2	48.5	19.9	3,400	4,000	1.95
<b>2217</b>	85	150	36	2	58	23.6	3,200	3,800	2.54
<b>2217K</b>	85	150	36	2	58	23.6	3,200	3,800	2.49
<b>2218</b>	90	160	40	2	70	28.7	3,100	3,600	3.19
<b>2218K</b>	90	160	40	2	70	28.7	3,100	3,600	3.12
<b>2219</b>	95	170	43	2.1	83.5	34.5	2,900	3,400	3.89
<b>2219K</b>	95	170	43	2.1	83.5	34.5	2,900	3,400	3.8
<b>2220</b>	100	180	46	2.1	94	38.5	2,700	3,200	4.65
<b>2220K</b>	100	180	46	2.1	94	38.5	2,700	3,200	4.54
<b>2221</b>	105	190	50	2.1	109	45	2,600	3,100	6.07
<b>2222</b>	110	200	53	2.1	124	51.5	2,500	2,900	7.1
<b>2222K</b>	110	200	53	2.1	124	51.5	2,500	2,900	6.94