

Bearing No.	Boundary dimensions (mm)					Basic load rating(kN)		Limiting speeds (rpm)		Weight(Kg)
	基本尺寸					额定负荷		极限转速		
型号	d	D	B	$r_{s\ min}$	$r_{s1\ min}$	Dynamic (Cr)	Static (Cor)	Grease	Oil	重量
				$r_{s\ 最小}$	$r_{s1\ 最小}$	动载	静载	脂	油	
N1005	25	47	12	0.6	0.3	15.1	14.1	16,000	19,000	0.091
N1006	30	55	13	1	0.6	19.7	19.6	14,000	16,000	0.128
N1007	35	62	14	1	0.6	22.6	23.2	12,000	15,000	0.176
N1008	40	68	15	1	0.6	27.3	29	11,000	13,000	0.217
N1009	45	75	16	1	0.6	31	34	9,900	12,000	0.276
N1010	50	80	16	1	0.6	32	36	8,900	11,000	0.291
N1011	55	90	18	1.1	1	37.5	44	8,200	9,700	0.435
N1012	60	95	18	1.1	1	40	48.5	7,500	8,800	0.467
N1013	65	100	18	1.1	1	41	51	7,000	8,200	0.477
N1014	70	110	20	1.1	1	58.5	70.5	6,500	7,600	0.689
N1015	75	115	20	1.1	1	60	74.5	6,100	7,100	0.727
N1016	80	125	22	1.1	1	72.5	90.5	5,700	6,700	0.965
N1017	85	130	22	1.1	1	74.5	95.5	5,400	6,300	1.01
N1018	90	140	24	1.5	1.1	88	114	5,100	5,900	1.31
N1019	95	145	24	1.5	1.1	90.5	120	4,800	5,600	1.38
N1020	100	150	24	1.5	1.1	93	126	4,600	5,400	1.43
N1021	105	160	26	2	1.1	105	142	4,300	5,100	1.81
N1022	110	170	28	2	1.1	131	174	4,100	4,800	2.3
N1024	120	180	28	2	1.1	139	191	3,800	4,400	2.4
N1026	130	200	33	2	1.1	172	238	3,400	4,000	3.63
N1028	140	210	33	2	1.1	176	250	3,200	3,800	3.98
N1030	150	225	35	2.1	1.5	202	294	3,000	3,500	4.7